



ACCESS DOORS

General Product Specifications

Description and Construction:

Smoothflo Access Doors are a semi recessed style door made from prime galvanised steel panels (1.2mm) and frames (2mm). Door panels are fully insulated and are 25mm thick as standard with 50mm available. Our doors are fitted with heavy duty handle set(s) and adjustable hinges. We use a one piece, heat welded, high quality PVC compression gasket to avoid cold bridging and ensure a positive seal. We carry 7 stock sizes (25mm panel) with other sizes made to order.

Our range encompasses both standard width & wider access doors suitable for filter removal/maintenance, these doors are designated by an F in the order code.

Reference Dimensions:

The following dimensions are for use as a general guide.



Order Code*	Handle	Overall Frame Size Width x Height	Plug Size Width x Height	Hole Size Width x Height	Clear Door Opening Width x Height
AD950	1	657mm x 1022mm	585mm x 950mm	595mm x 960mm	509mm x 874mm
AD1130	2	657mm x 1202mm	585mm x 1130mm	595mm x 1140mm	509mm x 1054mm
AD1400	2	657mm x 1472mm	585mm x 1400mm	595mm x 1410mm	509mm x 1324mm
AD950F	2	797mm x 1022mm	725mm x 950mm	735mm x 960mm	649mm x 874mm
AD1130F	2	797mm x 1202mm	725mm x 1130mm	735mm x 1140mm	649mm x 1054mm
AD1400F	2	797mm x 1472mm	725mm x 1400mm	735mm x 1410mm	649mm x 1324mm
AD1700F	2	797mm x 1772mm	725mm x 1700mm	735mm x 1710mm	649mm x 1624mm

* 50mm door panel available. Order codes for Access Doors, with 50mm insulated door panels are designated by '-50' added to the end of the code, eg. AD...-50.